

[54] MOUNT OF A PRINTED CIRCUIT BOARD  
ARRANGED IN A BIPARTITE HOUSING

[75] Inventors: Karl Breu, Groebenzell; Herbert  
Hoher, Germering, both of Fed. Rep.  
of Germany

[73] Assignee: Siemens Aktiengesellschaft, Berlin  
and Munich, Fed. Rep. of Germany

[21] Appl. No.: 85,369

[22] Filed: Aug. 14, 1987

[30] Foreign Application Priority Data

Sep. 4, 1986 [DE] Fed. Rep. of Germany ..... 3630196

[51] Int. Cl.<sup>4</sup> ..... H05K 7/12

[52] U.S. Cl. .... 361/398; 174/138 D;  
361/399; 379/428; 379/433

[58] Field of Search ..... 361/399, 398, 395;  
174/138 D, 138 G; 379/429, 433, 428

[56] References Cited

U.S. PATENT DOCUMENTS

3,356,904	12/1967	Yonkers	.....	361/399	X
3,627,930	12/1971	Tolman	.....	379/433	X
3,947,984	4/1976	Winrown	.....	174/138 D	X
4,167,772	9/1979	Baehne	.....	174/138 D	X
4,291,202	9/1981	Adams et al.	.....	379/433	X

FOREIGN PATENT DOCUMENTS

WP85/03613 8/1985 PCT Int'l Appl. .  
277156 1/1953 Switzerland ..... 379/433

OTHER PUBLICATIONS

Telecom Report No. 2, 1984, pp. 141-146, "Siemens  
miniset 200—ein Kompaktfernsprecher fur uberall."

Primary Examiner—R. R. Kucia

Attorney, Agent, or Firm—Hill, Van Santen, Steadman &  
Simpson

[57] ABSTRACT

The invention is directed to a mount of a resiliently elastic, planar printed circuit board in a housing having a curved shape and composed of two parts. The end regions of the printed circuit board are secured such that a temporary positional change of the printed circuit board is impossible. This is achieved by having at least one resilient fastening element in the form of a shackle projecting from one of the housing parts overlapping the printed circuit board and/or pressing thereagainst in interlocking fashion at at least one end region of the printed circuit board. The shackle has a length such that the printed circuit board conforms to a shape adapted to the shape of the housing part accepting it.

6 Claims, 1 Drawing Sheet

